


TDG-SHAKE TABLE

250 KG



Technical Specifications

Axis	Uniaxial
Loading Capacity	250 Kg
Maximum Stroke	±200 mm
Table Dimensions	1000 x 1000 mm
Maximum Speed	800 mm/s
Maximum Acceleration	±1g @ 250 Kg ±2g @ 100 Kg
Power Requirement	3.3 kW , Three Phase , 380-480 VAC 50 - 60 Hz
Maximum Operating Frequency	15 Hz

**SERVO ELECTRO MECHANICAL
SYSTEM**

**LOW FRICTION PRECISION LINEAR
GUIDANCE SYSTEM**

**STRONG GROUND ANCHOR HOLES
GRID MOUNTING HOLES**

TDG CONTROLBOX

Digital Servo Controller

- 1 x 16 Bit $\pm 10V$ Control Channel for Servo System
- 1 X 16 Bit $\pm 10V$ analog output for feeding the table position to DAQ system.
- Digital Encoder Input for Table Position
- Up to 4 kHz selectable PID control loop time
- Signal Generation (Contour Mode) up to 2 kHz
- Ethernet Connection to PC
- Advanced PID control with velocity and acceleration feed forwards, notch filter and lowpass filter.
- Emergency Stop Button
- Digital Relay Outputs for Enabling / Disabling Torque from Software



EASYTEST Shake Table

Shake Table CONTROL Software

- Labview Based, Customizable Graphical Programming
- Sine, Triangle, Saw tooth, Square, Sine Sweep, Sine Beat, Random/Transient, Classical Shock, Waveform Replication, Frequency and Amplitude Sweeping and combinations.
- Signal and Time History Generator
- Time History import from ASCII files, unlimited file size and continuous operation,
- Amplitude Matching function for Cyclic Applications to minimize errors.
- Filtering and Scaling of input data
- User defined profiles, load and saving of input data and settings as a project.
- Real time display of input and output displacement / acceleration, data acquisition channels.
- Acceleration-Velocity-Displacement Time History, FFT and Response Spectrum of input and output data. Test simulation.
- Easy Calibration for DAQ Channels (load cell, accelerometer, strain gauge type sensors, etc.)
- Digital Filter options for DAQ Channels. (Low pass, highpass, bandpass, bandstop with Butterworth, Bessel, Chebyshev, Inverse Chebyshev topologies)
- Viewer Panel for Post Processing and Seismic Analysis.
- Grahps palette for zooming, panning, cursor and resizability for all the graphs.

